



MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

Product Name	MB-10A / GRAY BUTYL TAPE
Chemical Name	ISOBUTYLENE/ISOPRENE/BUTENE/MINERAL FILLER BLEND
Chemical Family	ISOBUTYLENE/ISOPRENE/BUTENE/MINERAL FILLER BLEND

24 Hour Emergency Assistance
(713)805-5704

Health	Fire	Reactivity	PPE
0	1	0	B

General MSDS Assistance
1-800-288-9489

Hazard Rating = 0-least, 1-slight, 2-moderate, 3-high, 4-extreme

SECTION II - HAZARDOUS INGREDIENTS

The composition of this mixture may be proprietary information. In the event of a medical emergency, compositional information will be provided to a physician or nurse. This product is not hazardous as defined in 29 CFR 1910.1200.

SECTION III - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT

This product is an inert solid. If in eye, remove as one would any foreign object. Flush eyes with plenty of water.

INHALATION

Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

SKIN CONTACT

Remove contaminated clothing/shoes. Wash the area with hot soapy water. Use of a waterless hand cleaner will help remove product. If irritation persists, get medical attention.

INGESTION

If large amounts are ingested, get medical attention.

SECTION IV - OCCUPATIONAL EXPOSURE LIMITS

NOT APPLICABLE

SECTION V - HEALTH INFORMATION

EYE CONTACT

Particulates may scratch eye surfaces/cause mechanical irritation.

SKIN CONTACT

No significant health hazards identified.

INHALATION

No significant health hazards identified.

INGESTION

No significant health hazards identified.

CARCINOGEN OR POTENTIAL CARCINOGEN

National Toxicology Program	yes	I.A.R.C. Monographs	yes	OSHA	yes
	no		no		no
	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>

SECTION VI EMPLOYEE PROTECTION

EYE:

None required; however, use of eye protection is good industrial practice.

SKIN:

None required; however, use of protective clothing to minimize contact is good industrial practice.

INHALATION:

None required; however, use of adequate ventilation is good industrial practice.

SECTION VII - PHYSICAL DATA

Boiling Point, °F: N/A Specific Gravity: 1.50 - 1.70 Vapor Pressure (mm HG): N/A

Melting Point, °F: N/A Solubility in water: Negligible Vapor Density (AIR=1): N/A

Evaporation Rate (N-Butyl) Acetate =1): N/A pH: Neutral

Appearance and Odor: grey solid, essentially odorless

SECTION VIII - FIRE AND EXPLOSION HAZARDS

FLASH POINT AND METHOD:

N/A

FLAMMABLE LIMITS: % VOLUME IN AIR

Lower: N/A Upper: N/A

EXTINGUISHING MEDIA

Use water fog, foam, dry chemical or CO₂.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS

Caution. Do not enter confined space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure NIOSH/MSHA approved self-contained breathing apparatus. Cool Fire exposed containers with water.

UNUSUAL FIRE AND EXPLOSION HAZARDS

None identified.

SECTION IX - REACTIVITY

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS AND MATERIALS TO AVOID

Avoid heat, flame, and strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide and unidentified organic compounds may be formed during combustion.

SECTION X - SPECIAL PRECAUTIONS

Avoid contact with eyes, skin, and clothing. Store away from sources of ignition. KEEP OUT OF REACH OF CHILDREN.

SECTION XI - ENVIRONMENTAL PROTECTION

SPILL OR LEAK PROCEDURES

Recover spilled material and place in suitable containers for recycle or disposal. Dispose in accordance with applicable Federal, State or local regulations.

SECTION XII - TRANSPORTATION REQUIREMENTS

NOT D.O.T. REGULATED

SECTION XIII - REGULATORY DATA

The components of the product are listed on the EPA/TSCA Inventory of Chemical Substances.

The information contained herein is based on the data available to us and is believed to be correct. However, GSSI Sealants, Inc. makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. This information and product is furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of use thereof.

GSSI Sealants
3605 Willowbend, Suite 575
Houston, TX 77054
Phone (800) 288-9484
Fax: (888) 947-4925

Updated : 11/15/06

